

PREPARATION EQUIPMENT

MA008-01

Belt tension gauge	
Dial indicator or dial indicator with magnetic base	
Micrometer	
Mirror	Brake hose
Steel square	
Tachometer	
Torque wrench	
Vernier calipers	

COOLANT

MA00A-02

Item	Capacity	Classification
Engine coolant (w/ Heater)	13.6 liters (14.4 US qts, 12.0 Imp. qts)	Ethylene-glycol base

LUBRICANT

MA00C-02

Item	Capacity	Classification
Engine oil Drain and refill w/ Oil filter change w/o Oil filter change	3.9 liters (4.1 US qts, 3.4 Imp. qts) 3.6 liters (3.8 US qts, 3.2 Imp. qts)	API grade SG Energy-Conserving n multigrade and recommended viscosity oil
Standard Type Manual transaxle oil (w/ Differential oil)	4.2 liters (4.4 US qts, 3.7 Imp. qts)	API GL-3, GL-4 or GL-5 SAE 75W-90 or 80W-90
Viscous Coupling LSD Type Manual transaxle oil (w/ Differential oil)	3.9 liters (4.1 US qts, 3.4 Imp. qts)	API GL-3, GL-4 or GL-5 SAE 75W-90 or 80W-90